

SPRAY GRADE MSDS

**MATERIAL SAFETY DATA SHEET**

Supplier:

[www.liquidrubber.ca](http://www.liquidrubber.ca)

601 Burlington Street East  
 Hamilton, Ontario L8L 4J5  
 Tel: 905-528-5800 Fax: 905-528-8700  
 Toll Free: 1.866.979.0300

**(THIS PRODUCT NOT SUBJECT TO THE CONTROLLED PRODUCTS REGULATIONS)****SECTION 1 MATERIAL IDENTIFICATION**

**TRADE NAME:** Spray Grade

**CHEMICAL FAMILY:** Water suspension of petroleum derived hydrocarbons (polymer modified emulsified asphalt) and inert fillers.

**MATERIAL USE:** Protective Coating

**T.D.G. CLASSIFICATION:** NON REGULATED

**WHIMIS CLASSIFICATION:** NON REGULATED

**EMERGENCY TELEPHONE #:** 1-866-979-0300

**SECTION II HAZARDOUS INGREDIENTS**

COMPONENT	CAS#	% (BY MASS)	LC50 (ppm) (rat inhal)	LD50 (mg/kg) (rat oral)
Complex mixture of bitumens	n/a	40-70	n/a	n/a
anionic surfactants	n/a	0.5-2.0	n/a	n/a
water	7732-18-5	30-60	n/a	n/a
Polymer dispersion		5-25	n/a	n/a

**SECTION III PHYSICAL PROPERTIES**

## SPRAY GRADE MSDS

---

**Odour and appearance:** Brown liquid, slight resinous odour.

**Odour threshold:** n/a

**Specific gravity:** 1.00 (approx.).

**Coefficient of water/oil distribution:** n/a

**Vapour pressure (mm Hg):** 17 @20°C (water)

**Boiling point:** 100°C (water)

**Freezing point:** 0°C

**pH:** 7-13

**Vapour density (air = 1):** >1

**Evaporation rate (nBuAcetate = 1):** <1

**Volatiles %:** 40-60 (water)

**Solubility in water:** partially soluble

---

## SECTION IV FIRE & EXPLOSION DATA

---

**Means of extinction:** n/a

**Sensitivity to mechanical impact/static discharge:** n/a

**Flash point (method):** n/a (non-combustible)

**Upper flammable limits % :** n/a

**Lower flammable limits % :** n/a

**Autoignition temperature:** n/a

**Special fire fighting instructions:** n/a

**Unusual fire and explosion hazards:** Product will not burn but may splatter if temperature exceeds the boiling point.

---

## SECTION V REACTIVITY DATA

---

**Chemical stability:** Stable

**Incompatible materials:** Will react with alkaline sensitive materials such as acids and certain metals. Contact with reactive metals such as aluminium or magnesium will result in the formation of explosive hydrogen gas.

**Hazardous decomposition products:** Avoid heating above 200°C. At elevated temperatures hazardous vapours can be released, including carbon monoxide, hydrogen chloride, organic acids and aldehydes.

**Hazardous polymerization:** Will not occur.

---

## SECTION VI HEALTH INFORMATION

---

**Exposure limit:** n/a

**Inhalation:** n/a

**Skin:** adhesion

**Eyes:** adhesion, irritation.

**Ingestion:** Blockage of digestive and/or respiratory tract.

**Chronic effects:** n/a

## **EMERGENCY AND FIRST AID PROCEDURES**

**Inhalation:** n/a

**Skin:** This is an alkaline product. If splashed on the skin immediately wash thoroughly with fresh water. If the product has dried on the skin massage the area with medical grade mineral oil, baby oil or edible oil, then wash with soap and water. If irritation persists seek medical attention..

**Eyes:** Flush thoroughly with fresh water for at least ten minutes. Seek medical attention.

**Ingestion:** DO NOT INDUCE VOMITING. Seek medical attention.

---

## **SECTION VII SPILL PROCEDURES**

---

**In the event of a spill:** Dike and contain, transfer to containers for recovery or disposal. Keep out of sewers.

**Waste disposal method:** Follow federal, provincial and local regulations regarding disposal.

---

## **SECTION VIII SPECIAL PROTECTION**

---

**Respiratory protection:** n/a

**Ventilation:** n/a

**Protective gloves:** Recommended

**Eye protection:** safety glasses/splash goggles recommended

**Other protective equipment:** Long sleeves, loose clothing recommended.

---

## **SECTION IX SPECIAL PRECAUTIONS**

---

**Storage and handling conditions:** Keep containers tightly closed when not in use. KEEP FROM FREEZING.

**Special shipping information:** Not regulated by the Transportation of Dangerous Goods Regulations.

Prepared by: **Liquid Rubber Industries Inc.**

Preparation date: 22-June-07

Replaces: 21-Sep-05

The information contained herein is based on available data and is provided for information only. Liquid Rubber Industries Inc. makes no warranties, guarantees or conditions, expressed or implied, regarding the accuracy of the data or its use therein. Liquid Rubber Industries Inc. will not be liable for any damages arising from the use of the information or product described on this data sheet.